

**MASTER FLASH®**

**SOLAR  
METAL / TILED ROOFS**

**SOLAR  
METAL / TILED ROOFS**

# MASTER FLASH® SOLAR

## METAL ROOF



### SIZING CHART:

Check diameter of pipe. Select the appropriate Master Flash® Solar Flashing for any solar metal roof installation. Only use maximum pipe diameters on minimal roof angles.



**25**  
YEAR  
WARRANTY

### SIZING CHART FOR SOLAR METAL ROOF:

	Pipe Size	Compound	Part No.		Flashing Details	
<b>Mini Port #0</b>	0 - 20mm	Black EPDM	MFS0B		A- Top Closed	Closed
	1 x 0-9.6mm cable entry port	Grey EPDM	MFS0G		B- Cut to suit pipe size	0 - 20mm
		Red Silicone	MFS0S		C- Base dimensions	76mm
<b>Solar</b>	0 - 35mm	Black EPDM	MFS35B		A- Top Closed	Closed
	1 x 0-9.6mm cable entry port	Grey EPDM	MFS35G		B- Cut to suit pipe size	0 - 35mm
		Red Silicone	MFS35S		C- Base dimensions	100mm
<b>Middy</b>	0 - 50mm	Black EPDM	MFSMiddyB		A- Top Closed	Closed
	1 x 0 - 9.6mm cable entry port	Grey EPDM	MFSMiddyG		B- Cut to suit pipe size	0 - 50mm
		Red Silicone	MFSMiddyS		C- Base dimensions	96mm
<b>Solar Multi-Port Mini</b>	0 - 49mm	Black EPDM	MFMPMiniB		A- Top closed	Closed
	2 x 0 - 9.6mm cable entry ports	Grey EPDM	MFMPMiniG		B- Cut to suit pipe size	63.5mm
		Red Silicone	MFMPMiniS		C- Base dimensions	114mm
<b>Mult-Port #1</b>	6mm - 70mm	Black EPDM	MFMP1B		A- Top Closed	Closed
	2 x 0 - 9.6mm cable entry port	Grey EPDM	MFMP1G		B- Cut to suit pipe size	67mm
		Red Silicone	MFMP1S		C- Base dimensions	114mm
<b>Solar Flash</b>	19mm - 25mm	Black EPDM	MFSFB		A- Top opening diameter	16mm
		Grey EPDM	MFSFS		B- Cut to suit pipe size	63mm
					C- Base dimensions	101mm

# MASTER FLASH® MINI PORT #0

## METAL ROOF

Specifically  
designed for

# Metal Roofing

**25**  
YEAR  
WARRANTY

CODE: MFS0B



## 2 Port Design Multiple Functions



### Accommodates

1 x Ø - 20mm pipe / cable  
1 x Ø - 9.6mm pipe / cable



### Tight Space Problems

With a 76mm base size this flashing is one of the smallest on the market. Perfect for tight spaces and solar installations.



### Adaptable Base

The base is designed to mould to most panel configurations and roof pitches regardless of pipe location.



### Fire Retarding Agents

The addition of fire retarding agents milled directly into the rubber compound creates a self extinguishing feature.



# MASTER FLASH® SOLAR

## METAL ROOF

**25**  
**YEAR**  
WARRANTY



CODE: MFS35B

Available in:  
**2 Compounds**  
(Black or Grey EPDM  
& Red Silicone for extreme  
heat applications)

### One Design **Solar Applications**

- ✓ **Accommodates**  
1 x 0 - 35mm pipe / cable
- ✓ **Weather Protection**  
Made of EPDM or Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.
- ✓ **Adaptable Base**  
The base is designed to mould to most panel configurations and roof pitches regardless of pipe location.
- ✓ **Fire Retarding Agents**  
The addition of fire retarding agents milled directly into the rubber compound creates a self extinguishing feature.

# MASTER FLASH® SQUARE BASE MIDDY

## METAL ROOF

**25**  
**YEAR**  
**WARRANTY**



CODE: MFSMIDDYB

Available in:

### 2 Compounds

(Black or Grey EPDM  
& Red Silicone for extreme  
heat applications)

## 2 Port Design for Metal Roofs



### Accommodates

1 x Ø - 50mm pipe / cable  
1 x Ø - 9.6mm pipe / cable



### Weather Protection

Made of EPDM or Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.



### Adaptable Base

The base is designed to mould to most panel configurations and roof pitches regardless of pipe location.



### Fire Retarding Agents

The addition of fire retarding agents milled directly into the rubber compound creates a self extinguishing feature.



# MASTER FLASH® MULTI-PORT MINI METAL ROOF

**25**  
YEAR  
WARRANTY



CODE: MFMPMINIB

**5 Port  
Design  
for the  
HVAC  
Industry**

## One Design Multiple Functions

- ✓ **Accommodates**  
1 x Ø - 49mm pipe / cable  
2 x Ø - 9.6mm pipe / cable  
2 x Ø - 20mm pipe / cable
- ✓ **5 Port Design**  
Extra Ports to accommodate copper pipe  
and electrical cabling
- ✓ **Adaptable Base**  
114mm base to provide a good seal when  
only small space is available
- ✓ **Low Profile**  
Low profile boot to ensure the right bending  
of copper pipe
- ✓ **Fire Retarding Agents**  
The addition of fire retarding agents milled  
directly into the rubber compound creates a  
self extinguishing feature.



# MASTER FLASH® MULTI-PORT #1 METAL ROOF

Specifically  
designed for

## Metal Roofing

**25**  
YEAR  
WARRANTY



CODE: MFMP1B

Stainless  
Steel  
Gripper  
Included



CODE: MFMP1S

## 1 Design 2 Applications Multiple Functions

Up to 4 Cable or Wires per flashings.



✓ **Accommodates**  
1 x 6 - 70mm pipe / cable  
2 x 0 - 9.6mm pipe / cable

✓ **No hassle**  
One piece stainless steel gripper to  
secure retrofit applications

✓ **Fire Retarding Agents**  
The addition of fire retarding agents  
milled directly into the rubber  
compound creates a self extinguishing  
feature.

# MASTER FLASH® SOLAR FLASH

## METAL ROOF

Also suitable for  
Metal  
Roofs

**25**  
YEAR  
WARRANTY



CODE: MFSFB

Designed for  
19mm - 25mm  
Copper Pipe  
without the need  
for cutting



- ✓ **Accommodates**  
1 x 19 - 25mm pipe / cable
- ✓ **Round Base**  
The simple round base flashing is available in black EPDM or red silicone with a pre-cut hole for copper pipe sizes.
- ✓ **Pitch**  
The pitch canal allows for maximum flexibility, easily accommodating up to a 60° pitch without affecting performance.
- ✓ **Ozone and UV Protection**  
Flashings are made of EPDM and Silicone, and are designed for maximum resistance to all weather conditions.
- ✓ **Fire Retarding Agents**  
The addition of fire retarding agents milled directly into the rubber compound creates a self extinguishing feature.

# MASTER FLASH® SOLAR TILED ROOF METAL ROOF

## SIZING CHART:

Check diameter of pipe. Select the appropriate Master Flash® Solar Tiled Roof Product. Only use maximum pipe diameters on minimal roof angles.



**25**  
**YEAR**  
**WARRANTY**

## LEAD BASE - SOLAR TILED ROOF

	Pipe Size	Compound	Part No.		Flashing Details	
Solar Muti Port	0-49mm	Black EPDM	TFLDSB		A-Top opening diameter	0 - 49mm
	2 x 0-9.6mm cable entry port	Grey EPDM	TFLDSG		B-Overall height	63mm
	2 x 0-20mm cable entry port	Red Silicone	TFLDSS		C-Base dimensions	410 x 490mm
Solar Mini	0-20mm	Black EPDM	TFLDVMiniB		A-Cut to suit pipe size	0 - 20mm
	1 x 0-9.6mm cable entry port	Grey EPDM	TFLDVMiniG		B-Base dimensions	300 x 550mm
		Red Silicone	TFLDVMiniS			

## ALUMINIUM BASE - SOLAR TILED ROOF

	Pipe Size	Compound	Part No.		Flashing Details	
Solar Muti Port	0-49mm	Black EPDM	TFALSB		A-Top opening diameter	0 - 49mm
	2 x 0-9.6mm cable entry port	Grey EPDM	TFALSG		B-Overall height	63mm
	2 x 0-20mm cable entry port	Red Silicone	TFALSS		C-Base dimensions	410mm x 490mm
Solar Mini	0-20mm	Black EPDM	TFALVMiniB		A-Cut to suit pipe size	0 - 20mm
	1 x 0-9.6mm cable entry port	Red Silicone	TFALVMiniS		B-Base dimensions	300mm x 550mm

# MASTER FLASH® SOLAR FLASH

## METAL ROOF

Suitable for  
Tiled  
Roof

**25**  
YEAR  
WARRANTY



CODE: TFLDSB

### Powder Coated Safe Lead Base

- ✓ **Accommodates**  
1 x 0-49 mm pipe / cable  
2 x 0 - 9.6mm pipe / cable  
2 x 0 - 20mm pipe / cable
- ✓ **Lead Base**  
410mm x 490mm
- ✓ **Extra Ports**  
To accommodate Copper pipe and electrical cabling
- ✓ **Easy Install**  
for Solar applications
- ✓ **Fire Retarding Agents**  
The addition of fire retarding agents milled directly into the rubber compound creates a self extinguishing feature which enables it to be used with type "B" vents. Listed with IAPMO certification No.3121

Available in:  
**2 Compounds**  
(Black or Grey EPDM  
& Red Silicone for extreme  
heat applications)

# MASTER FLASH<sup>®</sup> SOLAR MINI

METAL ROOF

Extra Port  
for  
Thermostat  
Cables

**25**  
YEAR  
WARRANTY



CODE: TFLDVMINIB

## 2 Port Design Multiple Functions



### Accommodates

- 1 x 0 - 20mm pipe / cable
- 1 x 0 - 9.6mm pipe / cable



### Fire Retarding Agents

The addition of fire retarding agents milled directly into the rubber compound creates a self extinguishing feature.

# MASTER FLASH® TILE FLASH SOLAR METAL ROOF

## Lead and Aluminium Base Available

Available in  
**2 Compounds**  
(Black or Grey EPDM  
& Red Silicone for extreme  
heat applications)

		Black & Grey EPDM	Red SILICONE
ADVANCED OZONE RESISTANCE tested to...		70 hour @500 pphm	70 hour @500 pphm
HIGH TEMPERATURE RESISTANCE Tested to...	Intermittent	+135°C	+260°C
	Continuous	+100°C	+225°C
LOW TEMPERATURE RESISTANCE tested to...		-55°C	-74°C
COMPRESSION SET minimum...		25%	50%

\*Complete specification data and testing methods are available upon request.

- Suitable for potable water
- Environmentally friendly

Easy  
5 minute  
On-Site  
Installation

With **MASTER FLASH® 25 Year Warranty**,  
we've got it covered.

**25**  
**YEAR**  
WARRANTY