

Description

- EPDM rubber.
- Available in Black, Grey and Silicone Red.
- Also available in BHP roofing colours on request.
- Size range: 0mm to 1mt available.
- All EPDM Master Flash pipe flashings have a high temperature resistance of 135°C intermittently. A Silicone Red compound is also available, and this product has a high resistance of 260°C intermittently.
- Complies with BAL rating requirements.

1.30	R20.00	2.00
4.00 A	1	SECTION A-A SCALE 1 : 7

AZTEC	ļ.
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF	
AZTEC AUSTRALASIA. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AZTEC AUSTRALASIA IS	

В

APPLICATION		DO NOT SCALE DRAWING	
NEXT ASSY	USED ON	FINISH	
		MATERIAL	
		INTERPRET GEOMETRIC TOLERANCING PER:	Q.A
		THREE PLACE DECIMAL ±	MF
	ANGULAR: MACH±	ANGULAR: MACH± BEND ± TWO PLACE DECIMAL ±	ENG
		DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ±	DR.
		UNLESS OTHERWISE SPECIFIED:	

):		NAME	DATE	
	DRAWN			
	CHECKED			TITLE:
	ENG APPR.			
	MFG APPR.			
	Q.A.			
	COMMENTS:			
				SIZE

SIZE DWG. NO. AMF6B

SCALE: 1:10 WEIGHT: SHEET 1 OF 1

2

В

Δ

REV